

Butler Performance Super Flow SF-600 Metric Test Data

Customer Name: _____ Date: _____

Head Type: _Edelbrock Edelbrock Victor Pro-Port 11 degree

Flow Range	1	2	3	4	5	6
Exh:				327		
Int:				294.3	439.8	591.4

Intake	FR-4	FR-4	FR-5	FR-5	FR-5	FR-6	FR-6	FR-6
Valve Lift	0.200	0.300	0.400	0.500	0.600	0.700	0.800	0.900
Flow Scale	45.0		70.0		93.0		74.2	
		71.0		84.7		73.0		74.8
Corr CFM	132		308		409		438	
		209		373		431		442

Exhaust	0.200	0.300	0.400	0.500	0.600	0.700	0.800	0.900
Valve Lift	0.200	0.300	0.400	0.500	0.600	0.700	0.800	0.900
Flow Scale	32.0		49.0		74.6		81.4	
		48.0		68.0		79.0		82.6
Corr CFM	105		193		244		266	
		157		222		258		270
Int/Exh Ratio	80	75	63	60	60	60	61	61

Bore Size: _4.380_____

Test Pressure: _28"

Head CC: _____

Valve Dia: Int _____ Exh _____

Valve Angle: Int _____ Exh _____

Test Notes: _____
